COATING METHOD AND APPARATUS TO CREATE STONETEXTURE

Publication number: JP9201561
Publication date: 1997-08-05

Inventor: OGA

OGAWA YASUSHI; KOIZUMI MASASHI; TANI

TOSHIKAZU

Applicant:

KUBOTA KK

Classification:

- international:

B05D1/16; B05C9/02; B05D1/00; B05C9/00; (IPC1-7):

B05C9/02; B05D1/16


- European:

Application number: JP19960035666 19960129 Priority number(s): JP19960035666 19960129

Report a data error here

Abstract of JP9201561

PROBLEM TO BE SOLVED: To make a spotted pattern by paint droplets easily and surely and also a mixed color spotted pattern with two or more colors by one coating operation when natural stonetexture decorative coating is applied on the surface of stone. SOLUTION: In a coating method, a brush roll 2 is placed at a height not contacting the surface of a plate 1, and coating droplets are scattered by centrifugal force by rotating the roll 2 which is being supplied with coating 3 to be dropped on the plate 1. An apparatus for the method is composed of a conveyor 4 for transferring the plates 1, the brush roll 2 placed at a height not contacting the surface of the plate 1 on the upper surface of the conveyer 4, a coating supplying apparatus 5 for supplying the coating 3 continuously to the roll 2, a driving apparatus 6A for the roll 2, and a rotation controller 6B for the driving apparatus 6A.



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY



(11) Publication number:

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 08035666

(22) Application date: 29.01.96

(51) Intl. Cl.: **B05C** 9/02 B05D 1/16

(30) Priority:

(43) Date of application

publication:

05.08.97

(84) Designated contracting

states:

(71) Applicant: KUBOTA CORP

(72) Inventor: OGAWA YASUSHI

KOIZUMI MASASHI TANI TOSHIKAZU


(74) Representative:

(54) COATING METHOD AND APPARATUS TO CREATE STONETEXTURE

(57) Abstract:

PROBLEM TO BE SOLVED: To make a spotted pattern by paint droplets easily and surely and also a mixed color spotted pattern with two or more colors by one coating operation when natural stonetexture decorative coating is applied on the surface of stone.

SOLUTION: In a coating method, a brush roll 2 is placed at a height not contacting the surface of a plate 1, and coating droplets are scattered by centrifugal force by rotating the roll 2 which is being supplied with coating 3 to be dropped on the plate 1. An apparatus for the method is composed of a conveyor 4 for transferring the plates 1, the brush roll 2 placed at a height not contacting the surface of the plate 1 on the upper surface of the conveyer 4, a coating supplying annaratus 5 for sunniving the coating



3 continuously to the roll 2, a driving apparatus 6A for the roll 2, and a rotation controller 6B for the driving apparatus 6A.

COPYRIGHT: (C)1997,JPO

BEST AVAILABLE COPY